



# Townsend Bearings



## Adhesives, Sealants and Repair Compounds



Product	Operating Temp.	Paintable	Cure Method	Skin-Over Time	Viscosity	Especially For	Colour Variations
<b>Loctite 5145</b>	Up to 200°C	No	Moisture	70 min	Paste	Electrical Components	Translucent
<b>Loctite 5366 / 67 / 68</b>	Up to 250°C	No	Moisture	5 min	Paste	Glass	5366 - Clear 5367 - White 5368 - Black
<b>Loctite 5398</b>	350°C	No	Moisture	8-10 min	Liquid	Sealing/Potting	Red
<b>Loctite 5399</b>	Up to 350°C	No	Moisture	5 min	Paste	Oven Door Seals Heat source sealing	Red
<b>Loctite 5221 / 25/ 26</b>	Up to 80°C	Yes	Moisture	70 min	Paste	Flexible, medium strength bonds	5221 - Grey 5225 - White 5226 - Black
<b>Loctite 5062 / 63 / 64 / 65 / 66 / 68 / 69</b>	Up to 100°C	Yes	Moisture	15 min	Paste	Flexible bonds Joint sealing	<b>Low Strength</b> 5062 - Black 5063 - Grey 5064 - White <b>Medium Strength</b> 5065 - Black 5066 - Dark-Grey 5068 - White <b>High Strength</b> 5069 - Black