



Townsend Bearings



Adhesives, Sealants and Repair Compounds



| Product | Gasket Type | Flange Type | Cure Method | Tack-Free Time | Temp. Resistance | Instant Seal | Resistance Oil | Resistance Water/Glycol |
|---------------------|---------------------|-------------------|---------------------|----------------|------------------|--------------|----------------|-------------------------|
| Loctite 5203 | Formed-in-Place | Rigid | Anaerobic | N.A. | 150°C | Excellent | Excellent | Excellent |
| Loctite 3020 | Use with cut-gasket | Rigid or Flexible | Solvent Evaporation | N.A. | N.A. | Excellent | N.A. | N.A. |
| Loctite 574 | Formed-in-Place | Rigid | Anaerobic | N.A. | 150°C | Excellent | Excellent | Excellent |
| Loctite 518 | Formed-in-Place | Rigid | Anaerobic | N.A. | 150°C | Excellent | Excellent | Excellent |
| Loctite 510 | Formed-in-Place | Rigid | Anaerobic | N.A. | up to 200°C | Excellent | Excellent | Excellent |
| Loctite 5205 | Formed-in-Place | Rigid | Anaerobic | N.A. | 150°C | Excellent | Excellent | Good |
| Loctite 5910 | Formed-in-Place | Flexible | Moisture | 20 min | 200°C | Excellent | Excellent | Moderate |
| Loctite 5699 | Formed-in-Place | Flexible | Moisture | 10 min | 200°C | Excellent | Good | Excellent |