


Townsend Bearings



O Rings and Circlips

O-Rings: Quick Reference Guide to Standard Inch Sizes



Townsend Bearings

Size reference numbers quoted are in accordance with BS 1806:1989 and AS 568A:1984

Section					Section						Section				
I.D.	1/16	3/32	1/8	3/16	I.D.	1/16	3/32	1/8	3/16	1/4	I.D.	3/32	1/8	3/16	1/4
BS Number					BS Number						BS Number				
1/32	001				2 3/16		139				7	167	262	365	441
3/64	002				2 1/4	035	140	228	331		7 1/4	168	263	366	442
1/16	003	102			2 5/16		141				7 1/2	169	264	367	443
5/64	004				2 3/8	036	142	229	332		7 3/4	170	265	368	444
3/32	005	103			2 7/16		143				8	171	266	369	445
1/8	006	104			2 1/2	037	144	230	333		8 1/4	172	267	370	445A
5/32	007	105			2 9/16		145				8 1/2	173	268	371	446
3/16	008	106	201		2 5/8	038	146	231	334		8 3/4	174	269	372	446A
7/32	009	107			2 11/16		147				9	175	270	373	447
1/4	010	108	202		2 3/4	039	148	232	335		9 1/4	176	271	374	447A
5/16	011	109	203		2 13/16		149				9 1/2	177	272	375	448
3/8	012	110	204		2 7/8	040	150	233	336		9 3/4	178	273	376	448A
7/16	013	111	205	309	3	041	151	234	337		10		274	377	449
1/2	014	112	206	310	3 1/8			235	338		10 1/4				449A
9/16	015	113	207	311	3 1/4	042	152	236	339		10 1/2		275	378	450
5/8	016	114	208	312	3 3/8			237	340		10 3/4				450A
1 1/16	017	115	209	313	3 1/2	043	153	238	341		11		276	379	451
3/4	018	116	210	314	3 5/8			239	342		11 1/4				451A
13/16	019	117	211	315	3 3/4	044	154	240	343		11 1/2		277	380	452
7/8	020	118	212	316	3 7/8			241	344		11 3/4				452A
15/16	021	119	213	317	4	045	155	242	345		12		278	381	453
1	022	120	214	318	4 1/8			243	346		12 1/2				454
1 1/16	023	121	215	319	4 1/4	046	156	244	347		13		279	382	455
1 1/8	024	122	216	320	4 3/8			245	348		13 1/2				456
1 3/16	025	123	217	321	4 1/2	047	157	246	349	425	14		280	383	457
1 1/4	026	124	218	322	4 5/8			247	350	426	14 1/2				458
1 5/16	027	125	219	323	4 3/4	048	158	248	351	427	15		281	384	459
1 3/8	028	126	220	324	4 7/8			249	352	428	15 1/2				460
1 7/16		127	221		5	049	159	250	353	429	16		282	385	461
1 1/2	029	128	222	325	5 1/8			251	354	430	16 1/2		283	386	462
1 9/16		129			5 1/4	050	160	252	355	431	17		284	387	463
1 5/8	030	130	223	326	5 3/8			253	356	432	17 1/2				464
1 11/16		131			5 1/2		161	254	357	433	18			388	467
1 3/4	031	132	224	327	5 5/8			255	358	434	18 1/2				468
1 13/16		133			5 3/4		162	256	359	435	19			389	469
1 7/8	032	134	225	328	5 7/8			257	360	436	20			390	470
1 15/16		135			6		163	258	361	437	21			391	471
2	033	136	226	329	6 1/4		164	259	362	438	22			392	472
2 1/16		137			6 1/2		165	260	363	439	23			393	473
2 1/8	034	138	227	330	6 3/4		166	261	364	440	24			394	474
											25			395	475
											26				